

interior drywall primer **801 LINE**

American Pride® paints are high performance interior coatings which are low in odor during application and drying. These products are ideal for use in occupied areas because of their low odor and VOCs (Volatile Organic Compounds).

RECOMMENDED USE

Ideal for sealing new drywall. Can also be used over aged plaster and masonry. This product can also be used to prepare previously painted surfaces and tightly adhered wallpaper. Glossy surfaces should be dulled before priming.

This product can be used in occupied areas without typical odor complaints because of the very low odor during application and drying.

SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

New Surfaces:

Non-Bleeding Wood, Plaster:

American Pride® Interior Latex Primer

Drywall:

American Pride® Interior Latex Primer

Metal:

Not recommended

EQUIPMENT

Conv. Spray:	40 PSI TIP:704/FX
Airless Spray:	1800 - 2400 PSI TIP:.015" - .021"
Brush:	Polyester or Nylon
Roller:	3/8"- 1/2" Nap Cover
Pad:	Standard

*VOC level as determined on untinted paint within the precision of ASTM D 3960



This product meets Green Seal environmental standards for volatile organic compounds (VOCs) and other ingredients.

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

PACKAGING

Gallons, 5 Gallons

COLORS

White and Tinted White

Note: Can be tinted with up to 3 oz. of colorant.

SPECIFICATION DATA

Type:	Acrylic Latex
Finish:	Flat
» Sheen:	5 Max @ 85°
% Solids (varies with color):	
» By Weight:	42 ±2%
» By Volume:	25 ±2%
Wt./Gallon: (White only):	10.64 lbs.
Flashpoint:	212°F (PMCC)
VOC lbs./gal (max):	0*
VOC gm/ltr (max):	0*
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight
Thickness:	
» Dry:	1.0 mil
» Wet:	4.0 mil
Coverage:	350-400 sq. ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)