

# exterior low lustre 201 LINE

American Pride® paints are high performance exterior coatings which are low in odor during application and drying. These products are ideal for use in occupied areas because of their low odor and VOCs (Volatile Organic Compounds).

## RECOMMENDED USE

American Pride® Exterior Low lustre is a premium quality paint that provides durable color and protection for a variety of exterior surfaces. This product is ideal for previously painted or primed surfaces such as vinyl, aluminum siding, wood siding, masonry, shutters, fencing and hardboard.

## SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

### Wood:

American Pride® Multi-purpose Primer should be used to seal any unprimed drywall or patching.

### Vinyl or Aluminum siding:

Darker colors than the original siding should not be used due to the possibility of warping.

### Masonry:

Allow new stucco, plaster, and masonry to cure 30 days before priming with American Pride® Multi-purpose primer.

### Metal:

Prime with an appropriate primer before applying this product.

## EQUIPMENT

<b>Conv. Spray:</b>	40 PSI TIP: 704/FX
<b>Airless Spray:</b>	1800 - 2400 PSI TIP: .015" - .021"
<b>Brush:</b>	Polyester or Nylon
<b>Roller:</b>	3/8"-1/2" Nap Cover
<b>Pad:</b>	Standard

\*VOC level as determined on untinted paint within the precision of ASTM D3960

## THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

## LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 85°F (29°C).

## PACKAGING

Quarts, Gallons, 5 Gallons

## COLORS

- 1232 palette colors
- Computer color matching available

## SPECIFICATION DATA\*\*

<b>Type:</b>	100% Acrylic Latex
<b>Finish:</b>	Satin
» Sheen: at 85°	14 to 19 (Substrate Dependent)
<b>% Solids (varies with color):</b>	
» By Weight:	59 ±2%
» By Volume:	41 ±2%
<b>Wt./gallon (white only):</b>	11.83 lbs /gal
<b>Flashpoint:</b>	212°F (PMCC)
<b>VOC lbs./gal. (max):</b>	< 0*
<b>VOC gm./ltr. (max):</b>	< 0*
<b>Thinner:</b>	Water
<b>Clean-up:</b>	Soap and Water
<b>Dry Time:</b>	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight

Note: Adding large amounts of zero VOC colorant can dramatically slow dry/cure time.

<b>Thickness:</b>	
» Dry:	1.5 mil
» Wet:	4.0 mil
<b>Coverage:</b>	400 sq. ft./gal. (on smooth surfaces)
<b>Flame Spread Rate:</b>	Class A (0-25 on non-combustible surfaces)

\*\*Product Data is based on AP 203-W